


110 Connecting Hardwares

- Features:**
 - Meets and exceeds TIA/EIA 568-B standard.
 - Material UL listed 94V-O rated thermoplastic.
 - Accepts 22-24 AWG solid or stranded wire.
 - Accepts connecting blocks 3, 4 and 5 pair sizes.
 - Connecting blocks are 110 IDC type Phosphor Bronze termination.
 - Includes label identification.

Ordering Information


Part No.	Description
AD-110-WBP-200-2U	200 pairs 110 wiring block w/o legs, panel type in 2U
AD-110-WBP-100-1U	100 pairs 110 wiring block w/o legs, panel type in 1U
AD-110-WB-300	300 pairs 110 wiring block w/o legs
AD-110-WB-100	100 pairs 110 wiring block w/o legs
AD-110-WB-50	50 pairs 110 wiring block w/o legs
AD-110-WB-300L	300 pairs 110 wiring block with legs
AD-110-WB-100L	100 pairs 110 wiring block with legs
AD-110-WB-50L	50 pairs 110 wiring block with legs
AD-110-C5	5 pair wiring connector
AD-110-C4	4 pair wiring connector
AD-110-C3	3 pair wiring connector
AD-110WM	110 Wire management w/o legs
AD-110-WM-L	110 Wire management with legs
AD-110-WM-1U	110 Wire management w/o legs, panel type in 1U
AD-110LH	Designation label holder
AD-110DL	Designation label




Designation Label Holder With label



C3/C4/C5 Wiring Connector




110 Wire Management w/o legs




100PR Wiring Block w/o Legs



50PR Wiring Block w/o Legs



110 Wire Management with legs




300PR Wiring Block with Legs



100PR Wiring Block with Legs



50PR Wiring Block with Legs



300PR Wiring Block w/o Legs