


## 110 Patch Panels

### ◎ Basic Features:


- ☆ Being UL approved, the panels provide optimum performance, exceeding TIA/EIA 568-A & ISO/IEC 11801 requirement.
- ☆ Made of UL94V-0 high-impact and fire retardant ABS material.
- ☆ Insertion Life Cycle: 500 cycles (minimum)
- ☆ Available with/without legs on the block base. Panels without leg are suitable for mounting in the cabinets. Patch panels with legs are suitable for mounting on the wall.
- ☆ Available in 32, 50, 64, 100, 200, 300 pairs for selection.
- ☆ Accept 22-26 AWG (0.4mm-0.64mm) solid or stranded cable.
- ☆ Available in Cat 5e and Cat 6 options for selection.
- ☆ Come with wire management and cover for selection.
- ☆ Block base and wiring connectors can be ordered separately for maximum flexibility.
- ☆ Fit for connection between patch cords and consolidation points.
- ☆ Connecting blocks are 110 IDC type phosphor bronze termination.

### ◎ Product Highlights:

- ☆ Working in harmony with 110 wiring connectors, the Cat5e patch panels can be component and tested with significant margin up to 155 MHz and Cat 6 products can be component and channel tested with significant margin up to 250 MHz.
- ☆ 360 degree pair isolation enhances near-end crosstalk performance.
- ☆ The conductors on the 110 patch panel can be easily stripped during termination to save installation time.
- ☆ Come with wire management bars to secure the cables in place for ease of termination.
- ☆ Termination can be done easily with special tool.



110 Patch Panel Without Legs



110 Patch Panel With Legs

## 110 Wiring Connectors

### ◎ Basic Features:

- ☆ 4 and 5 pair 110 connectors available.
- ☆ Available in Cat5e and Cat 6 options.
- ☆ Contacts are plated with 2µm silver.

### ◎ Technical Parameters:


- ☆ Minimum Insertion Life Cycles: 1,000 cycles
- ☆ Operating Temperature: 0°C ~ +60°C
- ☆ Storage Temperature: - 40°C ~ +60°C
- ☆ Maximum Current Rating: 0.1A
- ☆ Maximum Direct Resistance Unbalance: 5 MΩ

### ◎ Product Highlights:

- ☆ Cat5e and Cat 6 connectors provide optimum performance for NEXT in support of 10G Ethernet application.
- ☆ Each panel comes with colored designation labels and independent pair separator to ensure easy plug and play installation.
- ☆ Can be marked with color designation label to identify the pair configuration on each connector.
- ☆ Accept both 110 and Krone type termination.
- ☆ Connectors are stackable for space saving.
- ☆ Easy insertion for ease of installation.



4 Pair Wiring Connector



5 Pair Wiring Connector

## 110 Backplanes

### ◎ Basic Features:

- ☆ Made of fine steel, not easily damaged by scratching.
- ☆ Designed for 110 system, suitable for data patch panels & cable management panels.
- ☆ 1U backplane fits for fixing the cable management panels in the cabinet; 2U backplane fits for fixing patch panels in the cabinet.

### ◎ Product Highlights:


- ☆ Light & durable.
- ☆ Specially designed for cable routing.

### ◎ Ordering Information:

Part No.	Description
AD-110C5E-WBP-200-2U	CAT5e 200 Pairs 110 Wiring Block w/o Legs (Panel Type in 2U)
AD-110C5E-WBP-100-1U	CAT5e 100 Pairs 110 Wiring Block w/o Legs (Panel Type in 1U)
AD-110C5E-WB-300	CAT5e 300 Pairs 110 Wiring Block w/o Legs
AD-110C5E-WB-100	CAT5e 100 Pairs 110 Wiring Block w/o Legs
AD-110C5E-WB-50	CAT5e 50 Pairs 110 Wiring Block w/o Legs
AD-110C5E-WB-300L	CAT5e 300 Pairs 110 Wiring Block with Legs
AD-110C5E-WB-100L	CAT5e 100 Pairs 110 Wiring Block with Legs
AD-110C5E-WB-50L	CAT5e 50 Pairs 110 Wiring Block with Legs
AD-110C5E-C5	CAT5e 5 pair Wiring Connector
AD-110C5E-C4	CAT5e 4 pair Wiring Connector
AD-110C6-WB-32	CAT6 32 Pairs 110 Wiring Block w/o Legs
AD-110C6-WB-48	CAT6 48 Pairs 110 Wiring Block w/o Legs
AD-110C6-WB-64	CAT6 64 Pairs 110 Wiring Block w/o Legs
AD-110C6-WB-96	CAT6 96 Pairs 110 Wiring Block w/o Legs
AD-110C6-WB-32L	CAT6 32 Pairs 110 Wiring Block with Legs
AD-110C6-WB-48L	CAT6 48 Pairs 110 Wiring Block with Legs
AD-110C6-WB-64L	CAT6 64 Pairs 110 Wiring Block with Legs
AD-110C6-WB-96L	CAT6 96 Pairs 110 Wiring Block with Legs
AD-110C6-C4	CAT6 4 pair Wiring Connector
AD-110LH	Designation Label holder
AD-110DL	Designation Label
AD-110-BB-1U	1U Backplane for Patch Panel/Cable Management Panel
AD-110-BB-2U	2U Backplane for Patch Panel/Cable Management Panel



1U Cable Management Panel



CAT5e 100 Pairs 110 Wiring Block w/o Legs



1U/2U 110 Patch Panel